

SECTION 1. IDENTIFICATION

1.1 Product Identifier UFix, U.Fix, KMK Urine Fixative

Product Form: Liquid Mixture, Clear

Product Description: U.Fix Buffer Urine Cytology Collection Fluid

Cat No.:

1.2 intended Use of the Product

Recommended Use Urine Cytology Preservative Uses advised against No information Availble

1.3 Name, Address, and Telephone of Responsible Party

Company SSN Solutions

5900 Balcones Dr

Suite 100

Austin, TX 78731

Email TechSupport@SSNSol.com

1.3 Emergency Telephone Number

Chemtrec US: (800) 424-9300 Chemtrec Intl: (703) 527-3887

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification Of the Substance or Mixture

GHS-US Classification

Flammable Liquid 3	H226
Acute Toxicity 4 (Oral)	H302
Eye Irritation 2A	H319
Skin Sensitizer 1	H317
Carcinogencity 1A	H350
Specific Target Organ Toxicity Single Exposure 1	H370
Specific Target Organ Toxicity Single Exposure 3	H336
Specific Target Organ Toxicity Repeated Exposure 2	H373

Full text of hazard classes and H-statements : see section 16

2.2 Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US):

Page 1 of 12 Revision Date: 2020-12-22







Hazard Statements:

H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer

H336 - May cause drowsiness or dizziness

H302 - Harmful if swallowed

H331 - Toxic if inhaled

H370 - Causes damage to organs

Precautionary Statements (GHS-US):

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P304 + P340 - IF INHALED: Remove to fresh air and keep at rest in a position

comfortable for breathing

P311 - Call a POISON CENTER or doctor/ physician

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection

2.2 Other Hazards

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No	GHS-US Classification	% w/w
Water	7732-18-5		40-50
Ethyl alcohol	64-17-5	Flammable Liquid 2, H225 Eye Irritation 2A, H319	50-60
Methyl Alcohol	67-56-1	Flammable Liquid 2, H225 Acute Toxicity 3 (Oral), H301 Acute Toxicity 3 (Dermal), H311 Acute Toxicity 3 (Inhalation:vapor), H331 Specific Target Organ Toxicity Single Exposure 1, H370	7-10
Isopropyl Alcohol	67-63-0	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336	2-6

Full text of the R-phrases and H-phrases: see section 16

Page 2 of 12 Preparation Date: 2021-01-15

SECTION 4. FIRST AID MEASURES

4.1 Description of First-aid Measures

General Advice: If symptoms persist, call a physician. Show this safety data sheet to the

doctor in attendance.

Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. Obtain medical attention. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact: Wash off immediately with plenty of water for at least 15 minutes.

Obtain medical attention. If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. Ingestion Clean mouth with water and drink afterward plenty of water. Do not induce vomiting without medical advice. Never give anything by

mouth to an unconscious person. Consult a physician.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. Obtain medical

attention. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a

physician.

Protection of First-aiders No special precautions required. Use personal protective equipment.

4.2 Most Important Symptoms and Effects Both Acute and delayed

May cause an allergic skin reaction. Breathing difficulties. Symptoms of an allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea, and vomiting.

meddadire, dizziriess, tirediress, nadsed, dira voimting.

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide. Cool closed containers exposed to fire with water spray.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to a source of ignition and flashback. Containers may explode when heated. Thermal decomposition can lead to the release of irritating gases and vapors. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2), Thermal decomposition can lead to the release of irritating gases and vapors.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressuredemand, MSHA/NIOSH (approved or equivalent), and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Page 4 of 12 Preparation Date: 2021-01-15

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Do not get in eyes, on the skin, or clothing. Wear personal protective equipment. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces, and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges. Pay attention to flashback. No information is available. Do not take internally.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers.

7.3. Specific end use(s)

Use in laboratories

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Ethyl Alcohol (64-17-5)			
USA ACGIH	ACGIH TWA (ppm)	1000 ppm	
		Confirmed Animal Carcinogen with Unknown	
USA ACGIH	ACGIH chemical category	Relevance to Humans	
USA ACGIH	Biological Exposure Indices (BEI)	40 mg/l Parameter: Acetone - Medium: urine -	
		Sampling time: end of shift at end of workweek	
		(background, nonspecific)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³	

Page 5 of 12 Preparation Date: 2021-01-15

USA NIOSH	NIOSH REL (TWA) (ppm)	1000 PPM
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Isopropyl alcohol (67-63-0)			
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm)	400 ppm	
USA ACGIH	ACGIH chemical category	Not Classifiable as Human Carcinogen	
USA ACGIH	Biological Exposure Indices (BEI)	40 mg/l Parameter: Acetone - Medium: urine -	
		Sampling time: end of shift at end of workweek	
		(background, nonspecific)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m³	
USA NIOSH	NIOSH REL (TWA) (ppm)	400 PPM	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	1225 mg/m³	
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm	
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm	

Methyl Alcohol (67-56-1)			
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm) 250 ppm	250 ppm	
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall	
		exposure	
USA ACGIH	Biological Exposure Indices (BEI)	15 mg/l Parameter: Methanol - Medium: urine -	
		Sampling	
USA OSHA	OSHA PEL (TWA) (mg/m3)	260 mg/m3	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
USA NIOSH	NIOSH REL (TWA) (mg/m3)	260 mg/m3	
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm	
USA NIOSH	NIOSH REL (STEL) (mg/m3)	325 mg/m3	
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm	
USA IDLH	US IDLH (ppm)	6000 ppm	
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm) 250 ppm	250 ppm	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Appearance Clear

Page 6 of 12 Preparation Date: 2021-01-15

U.Fix Buffer Urine Collection Fluid

SAFETY DATA SHEET

Physical State Liquid

Odor Characteristic Alcohol-Like Odor

Odor Threshold No data На 6.3-6.6 **Melting Point / Range** No data **Softening Point** No data **Boiling Point / Range** 80°C / 176°F 24°C / 75°F **Flash Point** No data **Evaporation Rate** No data **Evaporation Limits** Flammablity (solid, gas) No data No data **Explosion Limits Vapor Pressure** No data **Vapor Density** No data **Specific Gravity** No data

Bulk Density No data Liquid

Water Solubility Miscible Solubility in other solvents No data Viscosity No data

9.2. Other Information

No additional information available

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

None known.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Incompatible products, Excess heat, Keep away from open flames, hot surfaces,

and sources of ignition.

10.5. Incompatible Materials

Strong oxidizing agents. Strong acids. Aldehydes.

10.6. Hazardous Decomposition Products:

Carbon monoxide (CO), Carbon dioxide (CO2), Thermal decomposition can lead to the release of irritating gases and vapors.

Page 7 of 12 Preparation Date: 2021-01-15

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity (Oral) Oral: Harmful if swallowed.

Acute Toxicity (Dermal) Not classified Acute Toxicity (Inhalation) Not classified

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
Ethyl Alcohol	10470 mg/kg (Rat)	20ml/kg (Rat)	124.7 mg/L/4h (Rat)
Isopropyl Alchol	5840 mg/kg	13900 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
Methyl Alcohol	5628 mg/kg (Rat)	15800 mg/kg (Rabbit)	64000 ppm (Rat) 4 h 83.2 mg/L (Rat) 4 h

Skin Corrosion/Irritation Not classified

pH 6.3-6.6

Eye Damage/Irritation Causes serious eye irritation.

pH 6.3-6.6

Respiratory or Skin Sensitization May cause an allergic skin reaction.

Germ Cell Mutagenicity Not classified

Carcinogenicity May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure) May cause damage to organs through prolonged or repeated exposure.

Reproductive Toxicity Not classified

Specific Target Organ Toxicity (Single Exposure) Causes damage to organs. May cause drowsiness or dizziness.

Aspiration Hazard Not classified

Symptoms/Injuries After Inhalation High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion This material is harmful orally and can cause adverse health effects or death in significant amounts. This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death.

Chronic Symptoms May cause cancer. May cause damage to organs (nervous system) through prolonged or repeated exposure (inhalation).

Page 8 of 12 Preparation Date: 2021-01-15

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Contains no substances known to be hazardous to the environment or that are not degradable in waste treatment plants.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Isopropyl alcohol	1400000 μg/L LC50 96 h	13299 mg/L EC50 = 48 h	1000 mg/L EC50 > 96 h
(67-63-0)	9640 mg/L LC50 96 h	9714 mg/L EC50 = 24 h	1000 mg/L EC50 > 72 h
	11130 mg/L LC50 96 h		
Methyl Alcohol	Pimephales promelas:	EC50 > 10000 mg/L 24h	
(67-56-1)	LC50 > 10000 mg/L 96h		
Ethyl Alcohol	Fathead minnow	EC50 = 9268 mg/L/48h	EC50 (72h) = 275 mg/l
(64-17-5)	(Pimephales promelas)		(Chlorella vulgaris)
	LC50 = 14200 mg/l/96h		
	Fathead minnow		
	(Pimephales promelas)		
	LC50 = 14200 mg/l/96h		
	Fathead minnow		

12.2. Persistence and degradability

Persistence Persistence is unlikely, based on information available.

Degradation in sewage

treatment plant Contains no substances known to be hazardous to the environment or

not degradable in wastewater treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. It Will likely be mobile in the environment due to its volatility. Disperses rapidly in the air.

12.5. Results of PBT and vPvB assessment

No data available for assessment

12.6. Other adverse effects

Endocrine Disruptor

Page 9 of 12 Preparation Date: 2021-01-15

U.Fix Buffer Urine Collection Fluid

SAFETY DATA SHEET

Information This product does not contain any known or suspected endocrine

disruptors

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused

Products Waste is classified as hazardous. Dispose of in accordance with local

regulations.

Contaminated Packaging Dispose of this container to a hazardous or special waste collection

point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep the product and empty container away

from heat and sources of ignition.

Other Information Do not dispose of waste into the sewer. Waste codes should be

assigned by the user based on the application for which the product was used. Can be incinerated, when in compliance with local regulations.

SECTION 14. TRANSPORT INFORMATION

In accordance with DOT

UN number UN1170
UN proper shipping name ETHANOL

Transport hazard class(es) 3
Packing group III

In accordance with IATA

UN number UN1170 UN proper shipping name ETHANOL

Transport hazard class(es) 3
Packing group III

In accordance with IMDG

UN number UN1170 UN proper shipping name ETHANOL

Transport hazard class(es) 3
Packing group III
Flash point 24°

SECTION 15. REGULATORY INFORMATION

15.1. US Federal Regulations

Page 10 of 12 Preparation Date: 2021-01-15

SARA Section 313 (specific toxic chemical listings)

64-17-5 ethanol 67-63-0 isopropanol 67-56-1 methanol

TSCA (Toxic Substances Control Act)

All ingredients are listed.

California Proposition 65 - Chemicals known to cause cancer

This product contains chemicals known to the State of California to cause cancer. Ethyl Alcohol is included on the Proposition 65 list when it is used in alcoholic beverages.

California Proposition 65 - Chemicals known to cause reproductive toxicity for females

None of the ingredients is listed.

California Proposition 65 - Chemicals known to cause reproductive toxicity for males

None of the ingredients is listed.

California Proposition 65 - Chemicals known to cause developmental toxicity

None of the ingredients is listed.

15.2. US State Regulations

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16. OTHER INFORMATION

Full text of R-phrases referred to under sections 2 and 3

- R11 Highly flammable
- R67 Vapors may cause drowsiness and dizziness
- R36 Irritating to eyes
- R22 Harmful if swallowed
- R34 Causes burns
- R40 Limited evidence of a carcinogenic effect
- R43 May cause sensitization by skin contact
- R10 Flammable
- R23/24/25 Toxic by inhalation, in contact with skin and if swallowed

R39/23/24/25 - Toxic: danger of very serious irreversible effects through inhalation, in contact with skin, and if swallowed

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

Page 11 of 12 Preparation Date: 2021-01-15

U.Fix Buffer Urine Collection Fluid

SAFETY DATA SHEET

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H351 - Suspected of causing cancer

H370 - Causes damage to organs

H336 - May cause drowsiness or dizziness

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

NFPA Health Hazard

2 - Materials that, under emergency conditions, can cause

temporary incapacitation or residual injury.

NFPA Fire Hazard

3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient

temperature conditions.

NFPA Reactivity Hazard

0 - Material that in themselves are normally stable, even under

fire conditions.



This document is based on our current knowledge and is intended to describe the product for health, safety, and environmental requirements only. It should not, therefore, be construed as guaranteeing any specific property of the product.